

# Wall mounted unit

## FTXP-N9 + RXP-N9



comfora **INVERTER**



Onecta app



Energy saving during standby mode



3-D air flow



Practically inaudible

Discreet wall mounted unit providing high efficiency and comfort

- › Onecta app
- › Practically inaudible
- › Voice control
- › Silver allergen removal and air purifying filter
- › 3-D airflow: air is blown into all corners of a room
- › Ideal for above door installation

- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A++ in cooling and heating
- › Space saving contemporary wall mounted design

# FTXP-N9 + RXP-N9



Indoor unit		FTXP		20N9		25N9		35N9		
Dimensions	Unit	HeightxWidthxDepth	mm	286 x770 x225						
Weight	Unit		kg	9.00						
Air filter	Type	Removable / washable								
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/ High	m <sup>3</sup> /min	4.4 / 5.6 / 7.5 / 9.6		4.4 / 5.8 / 7.5 / 9.9		4.5 / 6.3 / 8.3 / 11.5	
		Heating	Silent operation / Low / Medium / High	m <sup>3</sup> /min	5.0 / 6.6 / 8.6 / 10.6				5.1 / 7.0 / 9.0 / 11.5	
Sound power level	Cooling		dB(A)	55				58		
	Heating		dB(A)	55				58		
Sound pressure level	Cooling	Silent operation/Low/High	dB(A)	19 / 25 / 39		19 / 26 / 40		20 / 27 / 43		
	Heating	Silent operation/Low/High	dB(A)	21 / 28 / 39		21 / 28 / 40		21 / 29 / 40		
Control systems	Infrared remote control			ARC480A78						
	Wired remote control			BRC073A1						


Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal) | See separate drawing for electrical data

Outdoor unit		RXP		20N9		25N9		35N9		
Dimensions	Unit	HeightxWidthxDepth	mm	556 x740 x343						
Weight	Unit		kg	24				26		
Sound power level	Cooling		dB(A)	-						
Sound pressure level	Cooling	High	dB(A)	46				48		
	Heating	High	dB(A)	47				48		
Operation range	Cooling	Ambient	Min.~Max.	°CDB		-10 ~-48				
	Heating	Ambient	Min.~Max.	°CWB		-15 ~-18				
Refrigerant	Type				R-32					
	GWP				675.0					
	Charge		kg	0.55 /-				0.70 /-		
Piping connections	Liquid	OD	mm	6.4				6.4		
	Gas	OD	mm	9.5				9.5		
	Piping length	OU - IU	Max.	m		20		20		
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)					
	Level difference IU - OU			Max.	m		12		12	
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50 /220-240						
Current - 50Hz	Maximum fuse amps (MFA)		A	16						

See separate drawing for operation range | See separate drawing for electrical data | Contains fluorinated greenhouse gases

Efficiency data		FTXP + RXP		20N9 + 20N9		25N9 + 25N9		35N9 + 35N9	
Cooling capacity	Nom.	kW		1.3 /2.00 /2.6		1.3 /2.50 /3.0		1.3 /3.50 /4.0	
Heating capacity	Nom./Max.	kW		1.30 /2.50 /3.50		1.30 /3.00 /4.00		1.30 /4.00 /4.80	
Power input	Cooling	Min./Max.		kW		0.31 /0.530 /0.72		0.31 /0.660 /0.72	
	Heating	Min.		kW		0.25 /0.520 /0.95		0.29 /0.690 /0.95	
Space cooling	Energy efficiency class			A++					
	Capacity	Pdesign	kW	2.00		2.50		3.50	
	SEER			7.20					
	Annual energy consumption			kWh/a	97		121		170
Space heating (Average climate)	Energy efficiency class			A++					
	Capacity	Pdesign	kW	2.20		2.40		2.80	
	SCOP/A			4.65					
	Annual energy consumption			kWh/a	663		728		845

Daikin Europe N.V. Naamloze Vennootschap - Zandvoordestraat 300 - 8400 Oostende - België - www.daikin.eu - BE 0412 120 336 - RPR Oostende



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN24-046

01/2024



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.