

**Important:**

! Tube endings shall not be produced using tools of any other manufacturer..







**4.3.2.2 Procedure for the ending of the tube for the cordless press series 300**

In principle, the procedure for the cordless press is similar to the procedure used for the mechanical press. For specific features see the manual as supplied with every cordless press.

**4.3.3 System connecting elements – couplings, transition pieces and T-pieces**

The manufacturer supplies a wide range of original connecting elements - see the Table 12.

**Table 12 – Original connecting elements**

Element description	Figure	Dimension	Article No.
<b>Couplings G-G</b> both sides with the same cylindrical thread designed flat gasket sealing		G3/8 – G3/8	14-040-301
		G1/2 – G1/2	14-040-302
		G3/4 – G3/4	14-040-303
		G1 – G1	14-040-304
		G5/4 – G5/4	14-040-305
<b>Couplings R-G</b> One side with a cylindrical thread for flat gasket sealing, the other side with a tight-on-thread taper male thread (for thread sealing)		R3/8 – G3-8	14-040-351
		R1/2 – G1/2	14-040-352
		R3/4 – G3/4	14-040-353
		R1 – G1	14-040-354
		R5/4 – G5/4	14-040-355
<b>Couplings G-Rp</b> One side with a male cylindrical thread for flat gasket sealing, the other side with a female tight-on-thread		Rp3/8 – G3-8	14-040-331
		Rp1/2 – G1/2	14-040-332
		Rp3/4 – G3/4	14-040-333
		Rp1 – G1	14-040-334
		Rp5/4 – G5/4	14-040-335
<b>Reduced coupling G-G</b> Both sides with male cylindrical threads for flat gasket sealing, each side of the reduced coupling has a different dimension thread		G1/4 – G3/8	14-040-311
		G3/8 – G1/2	14-040-312
		G1/2 – G3/4	14-040-313
		G3/4 – G1	14-040-314
		G1 – G5/4	14-040-315
<b>Transition pieces Cu WR</b> A copper socket with a union nut for flat gasket sealing		G1/2 * 15 mm	24-001-001
		G1/2 * 18 mm	24-001-002
		G3/4 * 18 mm	24-001-003
		G3/4 * 22 mm	24-001-004
		G1 * 28 mm	24-001-005
		G1 * 22 mm	24-001-006
		G3/4 * 15 mm	24-001-007
<b>T-pieces</b> All sides provided with a male cylindrical threads for flat gasket sealing		3 * G3/8	14-040-321
		3 * G1/2	14-040-322
		3 * G3/4	14-040-323
		3 * G1	14-040-324

NOTE Other accessories available on demand.